



<div> <div> </div> <div> </div> <div> 0 130 </div> </div>						
Start	Console	Data View	Graphs	Tables & Maps	DashXL	Trouble Codes
PID	Name	Value	Units	Min	Avg	Max
SAE.IAT	Intake Air Temperature	11 °C		9	11	14
SAE.ECT	Engine Coolant Temperature	83 °C		82	83	87
SAE.ACRF_SUP	A/C system refrigerant monitoring support	Not Supported		-	-	-
SAE.AIR_RDY	Secondary air system monitoring status	Not Complete		-	-	-
SAE.AIR_STAT	Commanded Secondary Air Status	Unknown ENM Value		-	-	-
SAE.AIR_SUP	Secondary air system monitoring support	Supported		-	-	-
SAE.CAT_RDY	Catalyst monitoring status	Not Complete		-	-	-
SAE.CAT_SUP	Catalyst monitoring support	Supported		-	-	-
SAE.CCM_RDY	Comprehensive component monitoring status	Complete		-	-	-
SAE.CCM_SUP	Comprehensive component monitoring support	Supported		-	-	-
SAE.DTC_CNT	Number of emission-related DTCs stored in this ECU	0		0	0	0
SAE.EGR_SUP	EGR system monitoring support	Not Supported		-	-	-
SAE.EVAP_SUP	Evaporative system monitoring support	Not Supported		-	-	-
SAE.FUEL_RDY	Fuel system monitoring status	Complete		-	-	-
SAE.FUEL_SUP	Fuel system monitoring support	Supported		-	-	-
SAE.FUELSYS1	Fuel system 1 status	CL-Fault		-	-	-
SAE.FUELSYS2	Fuel system 2 status	Unknown ENM Value		-	-	-
SAE.HCAT_SUP	Heated catalyst monitoring support	Not Supported		-	-	-
SAE.HTR_RDY	Oxygen sensor heater monitoring status	Not Complete		-	-	-
SAE.HTR_SUP	Oxygen sensor heater monitoring support	Supported		-	-	-
SAE.LOAD_PCT	Calculated Load Value	20.4 %		7.5	23.8	65.5
SAE.LONGFT1	Long Term Fuel Trim - Bank 1	-1.6 %		-3.1	-1.1	7.0
SAE.LONGFT3	Long Term Fuel Trim - Bank 3	-53.9 %		-55.5	-53.5	-45.3
SAE.MAF	Air Flow Rate from Mass Air Flow Sensor	4.01 g/s		3.23	14.06	112.49
SAE.MIL	Malfunction Indicator Lamp (MIL) Status	MIL Off		-	-	-
SAE.MIL_DIST	Distance Travelled While MIL is Activated	0 kms		0	0	0
SAE.MIS_RDY	Misfire monitoring status	Complete		-	-	-
SAE.MIS_SUP	Misfire monitoring support	Supported		-	-	-
SAE.O2S11.O2SV	Oxygen Sensor Voltage Bank 1 - Sensor 1	0.560 V		0.000	0.454	0.860
SAE.O2S12.O2SV	Oxygen Sensor Voltage Bank 1 - Sensor 2	0.730 V		0.000	0.681	0.905
SAE.O2S_RDY	Oxygen sensor monitoring status	Not Complete		-	-	-
SAE.O2S_SUP	Oxygen sensor monitoring support	Supported		-	-	-
SAE.O2SLOC11	Oxygen Sensor Location Bank 1 - Sensor 1	Present		-	-	-
SAE.O2SLOC12	Oxygen Sensor Location Bank 1 - Sensor 2	Present		-	-	-
SAE.O2SLOC13	Oxygen Sensor Location Bank 1 - Sensor 3	Not Present		-	-	-
SAE.O2SLOC14	Oxygen Sensor Location Bank 1 - Sensor 4	Not Present		-	-	-
SAE.O2SLOC21	Oxygen Sensor Location Bank 2 - Sensor 1	Not Present		-	-	-
SAE.O2SLOC22	Oxygen Sensor Location Bank 2 - Sensor 2	Not Present		-	-	-
SAE.O2SLOC23	Oxygen Sensor Location Bank 2 - Sensor 3	Not Present		-	-	-
SAE.O2SLOC24	Oxygen Sensor Location Bank 2 - Sensor 4	Not Present		-	-	-
SAE.OBDSUP	On Board Diagnostic System Type	EOBD		-	-	-
SAE.SHRTFT1	Short Term Fuel Trim - Bank 1	0.8 %		-5.5	0.4	7.0
SAE.SHRTFT3	Short Term Fuel Trim - Bank 3	-52.3 %		-58.6	-52.7	-46.1
SAE.SPARKADV	Ignition Timing Advance for #1 Cylinder	12.0 °		-6.0	19.5	40.5
SAE.TP	Absolute Throttle Position	3.1 %		2.4	13.7	100.0
SCRIPT.FUEL_FR	Fuel Flow Rate	1.364 l/hr		1.099	4.840	38.262